



DOT-A



DOT-B



DOT-C

. Material :	Body : Anodized Aluminium	. Epoxy Paint :	Optional
	-		
	Frosted PMMA glass		
. Fixing :	Wall		
. LED Source :	1x4 LED 3 SDCM - L90B10 at 100.000hr	. Operating T° :	-20°C/+40°C
. Color T° :	2700K / 3000K / 4000K - Other possible temperatures. RGBW		
. Luminous flux :	Contact us	. Typ. Efficacy :	Contact us
. CRI :	80+ / 90+	. UV Resistance :	-
. Optic :	Diffuse	. High pressure :	No
. Adjustable :	Contact us	. Water Resistance :	IP67
. Weight :	0.7Kg	. Impact :	-
. Dimensions :	DOT-A: Ø66x50mmx64mm (or custom) DOT-B: Ø66x47mmx50mm (or custom) DOT-C: Ø66x47mmx32mm (or custom)	. Static load :	-
. Power supply :	700mA / 24VDC	. Protection Class :	Class III
. Max Power :	9.1W	. Energy Class :	G
. Control :	On-Off / 1-10V / DALI / DMX (with adequate driver)	. Driver :	Remote
. Cables :	1ml standard AD8 - (2x0.50mm ² black) - 1 Channel 3ml standard AD8 - (6x0.22mm ² black) - 3 Channels		
. Norms :	NF-EN 60529/60598-1/60598-2-1/60598-2-3/60598-2-5/62471		
. Warranty :	2 years standard (extendable to 5 years on demand)		