


GEMINI BOL (2025-00)

Ground recessed luminaire with a «blade of light» effect



. Material :	Body : Anodized Aluminium Anodized Aluminium - Stainless steel 316L - Brass Tempered glass extra white	. Epoxy Paint :	Optional
. Fixing :	Recessed		
. LED Source :	COB LED 3 SDCM - L90B10 at 100.000hr	. Operating T° :	-20°C/+40°C
. Color T° :	2700K / 3000K / 4000K - Other possible temperatures. DynW / RGBW		
. Luminous flux :	67lm (at 2700K-12°)	. Typ. Efficacy :	11lm/W
. CRI :	80+ / 90+	. UV Resistance :	-
. Optic :	WW(4°x170°)	. High pressure :	No
. Adjustable :	No	. Water Resistance :	IP68
. Weight :	1.7 Kg	. Impact :	IK09
. Dimensions :	Ø 146mm / Ø 160mm	. Static load :	-
. Power supply :	500mA / 230VAC	. Protection Class :	Class III
. Max Power :	6.3W - 9W	. Energy Class :	G
. Control :	On-Off / 1-10V / DALI / DMX (with adequate driver)	. Driver :	Remote
. Cables :	1ml standard AD8 - (2x0.50mm ² black) 1 Channel 3ml standard AD8 - (4x0.22mm ² black) 2 Channel / (8x0.22mm ² black) 4 Channels		
. Norms :	NF-EN 60529/60598-1-A1/60598-2-1/60598-2-3-A1/60598-2-5/62471		
. Warranty :	2 years standard (extendable to 5 years on demand)		