



A = 328mm 614mm 900mm
4LED 8LED 12LED

. Material :	Body : Anodized Aluminium	. Epoxy Paint :	Optional
	-		
	PMMA glass		
. Fixing :	Surface mounted		
. LED Source :	4 / 8 / 12 LED 3 SDCM - L90B10 at 100.000hr	. Operating T° :	-20°C/+40°C
. Color T° :	2700K / 3000K / 4000K - Other possible temperatures.		
. Luminous flux :	1600lm (at 3000K-4LED-12°)	. Typ. Efficacy :	96lm/W
. CRI :	80+ / 90+	. UV Resistance :	-
. Optic :	8° / 12° / 24° / 30° / 50° / ASY / WW(12°x62°) / WW(24°x62°) / EL(21°x92°) / ASY_247	. High pressure :	No
. Adjustable :	Yes	. Water Resistance :	IP67
. Weight :	0.7Kg / 1.1Kg / 1.6Kg	. Impact :	IK09
. Dimensions :	328mm (4 LED) / 614mm (8 LED) / 900mm (12 LED) x59mm	. Static load :	-
. Power supply :	1400mA	. Protection Class :	Class III
. Max Power :	18W - 54W	. Energy Class :	F
. Control :	On-Off / 1-10V / DALI (with adequate driver)	. Driver :	Remote
. Cables :	1ml standard AD8 - (2x0.50mm ² black) - 1 Channel		
. Norms :	NF-EN 60529/60598-1/60598-2-1/60598-2-3/60598-2-5/62471		
. Warranty :	2 years standard (extendable to 5 years on demand)		