


LUCIOLES (2025-00)

Luminous shapes for beaconing in frosted PMMA



. Material :	Body : Anodized Aluminium	. Epoxy Paint :	Optional
	-		
	Frosted PMMA glass		
. Fixing :	Fixed base or on bracket		
. LED Source :	1 LED 3 SDCM - L90B10 at 100.000hr	. Operating T° :	-20°C/+40°C
. Color T° :	2700K / 3000K / 4000K - Other possible temperatures. RGBW		
. Luminous flux :	Contact us	. Typ. Efficacy :	Contact us
. CRI :	80	. UV Resistance :	-
. Optic :	Frosted	. High pressure :	No
. Adjustable :	Contact us	. Water Resistance :	IP68
. Weight :	-	. Impact :	IK09
. Dimensions :	Custom size	. Static load :	-
. Power supply :	Contact us	. Protection Class :	Class III
. Max Power :	Contact us	. Energy Class :	Contact us
. Control :	On-Off / 1-10V / DALI / DMX (with adequate driver)	. Driver :	Remote
. Cables :	1ml standard AD8 - (2x0.22mm ² black) - 1 Channel 3ml standard AD8 - (8x0.22mm ² black) - 4 Channels		
. Norms :	NF-EN 60529/60598-1/60598-2-1/60598-2-3/60598-2-5/62471		
. Warranty :	2 years standard (extendable to 5 years on demand)		