




MICRO LINE

Thin linear spotlight



Diffusing resin



- . **Material:** Body in Anodized aluminium (Epoxy paint possible)
Full silicone encapsulation
- . **Fixing :** Surface mounted
- . **LED Source :** 9/18/27/36/45/54 LED 3-SDCM - L90B10@100.000hr
- . **Color T° :** 2700K / 3000K / 4000K - Other possible temperatures, contact us.
DynW / RGBW
- . **Product flux :** 520lm (9LED) – 3120lm (54LED)
- . **Efficacy :** 115lm/W
- . **CRI :** 80+ / 90+
- . **Optic :** 120°

- . **Adjustable :** Yes
- . **Dimensions :** 300mm/600mm/900mm x 30mm
- . **Weight :** 0.15Kg/0.59Kg

- . **Protection :** IP68
- . **Impact :** -
- . **Static load :** -
- . **High pressure :** No

- . **Protection :** Classe III
- . **Power :** 5W (9LED) – 30W (54LED)
- . **Power supply :** 500mA
- . **Driver :** Remote
- . **Control :** On-Off / 1-10V* / DALI* / DMX* (with adequate driver)
*Optional control through smartphone bluetooth CASAMBI

- . **Cables :** 1ml standard (2 x 0.22mm² noir) - Monochrome
3ml standard (4 / 6 x 0.22mm² noir) - DynW/RGBW

- . **Energy class:** E
- . **Norms :** NF-EN 60529/60598-1/60598-2-1/60598-2-3/60598-2-5/62471
- . **Warranty:** 2 years standard