



NIKO BLADE (2025-00)

1 LED spotlight with «blade of light» effect



. Material :	Body : black Anodized Aluminium Bracket : black Anodized Aluminium	. Epoxy Paint :	Optional
	-		
	Tempered glass extra white		
. Fixing :	Surface mounted		
. LED Source :	1 LED 3 SDCM - L90B10 at 100.000hr	. Operating T° :	-20°C/+40°C
. Color T° :	2700K / 3000K / 4000K - Other possible temperatures.		
. Luminous flux :	150lm (at 3000K)	. Typ. Efficacy :	55lm/W
. CRI :	80+ / 90+	. UV Resistance :	-
. Optic :	WW(12°x62°)	. High pressure :	No
. Adjustable :	Yes	. Water Resistance :	IP68
. Weight :	0.3Kg	. Impact :	-
. Dimensions :	□40mmx35mmx76mm	. Static load :	-
. Power supply :	900mA / 12-24VDC	. Protection Class :	Class III
. Max Power :	2.9W - 3.8W	. Energy Class :	G
. Control :	On-Off / 1-10V / DALI (with adequate driver)	. Driver :	Remote
. Cables :	1ml standard AD8 - (2x0.22mm ² black) - 1 Channel		
. Norms :	NF-EN 60529/60598-1/60598-2-1/60598-2-3/60598-2-5/62471		
. Warranty :	2 years standard (extendable to 5 years on demand)		