



FLEX-AT


Flexible dotless strip LED for outdoor use




TOP




SIDE



SIDE



TOP



- . **Material :** Polyurethane housing
- . **Fixing:** Anodized Aluminium beam
- . **Source :** 112 LED / ml – 3 SDCM – L70B50 @ 50.000hr
- . **Colour T° :** 2700K / 3000K / 4000K - Other possible temperatures, contact us.
RGB
- . **Product Flux :** 138 lm/m - 680 lm/m - side / 165 lm/m -> 1290 lm/m - top
- . **Efficacy :** 71 lm/W - side / 89 lm/W - top
- . **CRI :** 80+ / 90+
- . **Optic :** 112°
- . **Operating T° :** -25°C to +50°C

- . **Adjustable :** No
- . **Dimensions :** 15mm x 19mm (L_{max} = 4.5m)
- . **Weight :** 0.5kg/m

- . **Protection :** IP67 (< 1ml)
- . **Resistant :** UV rays, Salt and Solvents
- . **Impact :** -
- . **Static Load :** -
- . **High Pressure :** No

- . **Protection :** Classe III
- . **Power :** 1,9W - 9,6 W/ml - side / 1,9W -> 14,4 W/ml - top
- . **Power supply :** 24 VDC – Stabilized Current
- . **Driver :** Remote
- . **Control :** On-Off / 1-10V* / DALI* / DMX* (with adequate driver)
*Optional control through smartphone bluetooth CASAMBI
- . **Cable :** 150mm – 2000mm

- . **Energy class :** F
- . **Norms :** EN
- . **Warranty:** 2 years standard (possible extension)