




. Material :	Body : Anodized Aluminium	. Epoxy Paint :	Optional
	-		
	Tempered glass extra white		
. Fixing :	Surface mounted		
. LED Source :	1x4 LED 3 SDCM - L70B10 at 50.000hr	. Operating T° :	-20°C/+40°C
. Color T° :	2700K / 3000K - Other possible temperatures. DynW / RGBW		
. Luminous flux :	67lm	. Typ. Efficacy :	11lm/W
. CRI :	80+ / 90+	. UV Resistance :	-
. Optic :	4°x170°	. High pressure :	No
. Adjustable :	± 15°	. Water Resistance :	IP67
. Weight :	0.4Kg	. Impact :	IK09
. Dimensions :	Ø75mmx59mm	. Static load :	-
. Power supply :	500mA	. Protection Class :	Class III
. Max Power :	6.3W	. Energy Class :	G
. Control :	On-Off / 1-10V / DALI / DMX (with adequate driver)	. Driver :	Remote
. Cables :	1ml standard AD8 - (2x0.50mm ² black outside) - 1 Channel 3ml standard AD8 - (4/8x0.22mm ² black outside) - 2/4 Channels		
. Norms :	NF-EN 60529/60598-1-A1/60598-2-1/60598-2-3-A1/60598-2-5/62471		
. Warranty :	2 years standard (extendable to 5 years on demand)		